

America's Favorite Doors®

# AVANTE

GARAGE DOORS

## **CARE AND MAINTENANCE**

#### This manual covers the following:

- ANNUAL MAINTENANCE
- CLEANING & PRESERVING THE DOOR
- REPAIRING OR PAINTING DOOR
- WINDOW CLEANING
- WARRANTY INFORMATION

MODEL

SIZE

S/N

PID#

### Let us know what you think!

open camera and point




#### **REVIEW YOUR DOOR**

clopaydoor.com/leave-a-review

**REGISTER YOUR DOOR** 

clopaydoor.com/warranty-registration





For any questions please contact Clopay Consumer Services at 800-225-6729 or visit our chat line at www.clopaydoor.com

open camera and point



To review our installation instructions visit: clopaydoor.com/owners-manuals

open camera and point



For how-to videos and additional service and support information visit: clopaydoor.com/residential/support

#### PERIODIC MAINTENANCE

Your door will need regular inspection, lubrication and cleaning. The following checklists will help keep your door and its parts in good working order and help protect it from the elements.

#### **▲** WARNING

A sectional garage door is a large, heavy object that moves with the help of springs under high tension. Springs, bottom brackets, cables and associated hardware are under high tension and can cause death, serious injuries or damage to the door if not properly handled. For your safety and the safety of others, follow these instructions:


- **A DO NOT** loosen or remove bottom bracket with the spring tension engaged. You could suddenly release spring forces and risk severe injury.
- **A** DO NOT operate door with a broken spring. The sectional garage door is a large, heavy object that could cause physical strain and severe injury.
- ▲ DO NOT manually operate door if handles are not installed or functioning properly. In particular, do not place fingers in section joints in order to close the door, as finger pinch, crush or amputation will result. The lift handles are located for safe operation as well as easy use.
- **A DO NOT** operate door if it is too difficult to move, opens too quickly or the rollers come out of the track. The sectional garage door that is difficult to move could cause physical strain and severe injury.
- **A DO NOT** operate the door if glass or interior window retainer appears to be loose, cracked or warped. Failure to do so may result in glass falling out of the panel, causing property damage, serious injury or death.
- **A** DO NOT remove screws on inside retainer. Failure to do so may result in glass falling out of the panel, causing property damage, serious injury or death.

**DO** review all warnings on the door. If warnings are missing, please contact your professional installing Clopay Dealer, as instructed below. For assistance with these maintenance steps, repair or replacement of any parts, please contact vour professional installing Clopav Dealer: https://www.clopavdoor.com/where-to-buv

#### VISUAL INSPECTION CHECKLIST

Monthly inspection of the door and all of its components is recommended. If something seems out of balance or adjustment, or you note any of the following, please contact your Clopay Dealer or Clopay Consumer Services at 800-225-6729.

#### Visually inspect the door when in the down position for:





Open camera and point. To download a visual of the safety containment cable visit http://clopaypdfs. com/pdf\_files/SUP-

0137180\_EN.pdf

Worn or frayed cables. ☐ Loose, cracked, or warped glass panels or inside glass retainers. Inside the door, the plastic retainer holding the glass and its fasteners should appear secure.

Tears or gaps in the bottom weatherseal or perimeter seal.
Any covered, ripped, damaged or missing warning labels.

-		-	-	-					
Any missing,	broken, loo	se or malfur	ctioning do	oor handles.	There should	be two lifting	g points or	the ou	tside
and two on th	he inside of	the garage of	door.						

Inspect the warning labels.


#### **INSPECTING WINDOW AND/OR ALUMINUM PANELS**

We recommend that you inspect your window and/or aluminum panels every twelve months, at a minimum.

A WARNING If glass or retainers appear to be or feel loose, warped, cracked, broken, shrunken or misshaped, immediately discontinue use of the door. Failure to do so may result in glass falling out of the panel, causing property damage, serious injury or death. Contact your Clopay dealer or Clopay Consumer Services at 800-225-6729 for assistance.

#### Inspect the window and aluminum panels.

- 1. With the door closed and locked, disconnect the garage door opener.
- 2. From inside and outside the garage, visually inspect all panels to ensure they are not loose, cracked or warped.
- 3. From inside the garage, visually inspect the edge of each panel retainer for any shrinkage, loosening, cracking, warping or misshaping. Proper retainers should not show any gaps in the corner(s) of the window areas and should appear flat, straight and flush with the window/aluminum panel.
- **4.** Physically inspect the retainers by pressing the center of each retainer. You should feel little to no movement and not be able to compress the retainer more than 1/8".



#### DOOR OPERATION CHECKLIST

We recommend that at least twice per year after you have visually inspected the door and all of its components to:

#### Check the balance of the door.

- 1. With the door in the down position, detach the opener (if applicable) by pulling down on the red manual release handle.
- 2. Next, lift the door manually up to the halfway point and gently release the door. A balanced door should hang in place and not raise or lower. If the door does not stay in place contact your Clopay Dealer for adjustment.
- Check the door operation.
- 1. Once you have determined your door is in balance, lift the door up and down to ensure smooth operation. The door should be easily controlled when lifting and lowering.

**NOTE:** Be sure to reattach the opener once you confirm the door is operating properly.

#### ■ Safety feature for doors with automatic operators.

- **1.** Make sure that the operator has a working safety feature. Photo eyes should be mounted to the left and right sides of the bottom of the door opening.
- 2. Make sure any door locks are disabled or removed if the door has an automatic operator.
- 3. Retest following opener manufacturer's instructions.

#### **LUBRICATE THE DOOR**

Hinges

At least twice per	r year	lubricate	all moving	parts	of the	door	with	Clopay	Garage	Door	Pro	Lube	or a	synthetic
lubricant:														

IU	dill.
	☐ Lift cables at bottom bracket button
	Lock hardware where surfaces turn or slide
	Full length of torsion spring to reduce friction between coils
	Rollers at the bearing (but not the tire)





106430735

#### CLEANING AND PRESERVING THE DOOR

Doors must be cleaned at least twice a year, or four or more times a year for harsh environments (such as coastal regions, high road salts, etc.). If salt or other corrosive materials build up on the door and are visible, the door must be cleaned to avoid rust or other issues.

NOTICE

Failure to do so may result in loss of warranty coverage.

 $\label{lem:contact} \textbf{For further questions about the requirements, contact Clopay Consumer Services.}$ 

- Helps prevent damage caused by foreign matter or salt adhering to the door.
- Assists to restore the look of factory-applied finish by removing dirt and chalking.

#### **CLEANING THE DOOR**

Working from top to bottom of the door, use a well-soaked cloth, sponge or soft bristle brush with either of the following solutions:

- Household solution such as Dawn® dishwashing detergent may be used to clean more soiled areas.
- A fine scouring pad may be used for heavy surface soils. Be sure to scrub with the direction of the metal grain and do not apply too much pressure.
- **DO NOT** use scouring powders or solvents, alkaline or acid cleaners. Avoid cleaning in the hot sun.
- Rinse door with clean water to complete cleaning and allow to dry.

**NOTE:** Be sure to clean behind stop molding on the sides and top of the door. Refer to "Window Care" for detail on window cleaning on the next page. **DO NOT** use a pressure washer on the door

#### REPAIRING OR PAINTING THE DOOR

Surface damage can be easily repaired providing the damage is slight; such as a small scratch or rub mark.

#### REPAIRING OR PAINTING — ANODIZED ALUMINUM FINISH DOOR

Rub marks can be removed with a mild abrasive pad such as the Scotch-Brite<sup>™</sup> pad prior to touch-up painting.

**NOTE:** DO NOT sand the anodized material when touching up.

- Clean the area to be touched up with denatured alcohol to remove moisture.
- Apply the provided touch-up paint very sparingly as this is intended for small blemishes less than a few square inches.

**NOTE:** For more severe damage or repainting we recommend contacting a professional who specializes in the refinishing of architectural metals.

#### REPAIRING OR PAINTING — PAINTED ALUMINUM FINISH DOOR

- Minor damage to the painted surface should be sanded prior to application of the touch-up paint.
- Clean the area to be touched up with denatured alcohol to remove moisture.
- Apply the provided touch-up paint very sparingly as this is intended for small blemishes less than a few square inches

**NOTE:** For more severe damage or repainting we recommend contacting a professional who specializes in the refinishing of architectural metals.

#### WINDOW CARE

- Clean with a mild solution of a dishwashing detergent and a soft cloth. DO NOT use any ammoniated, abrasive
  or solvent-based cleaners of any kind.
  - For acrylic or polycarbonate windows: These windows CAN ONLY be washed using a clean, soft sponge
    or cloth with a mild dish soap and lukewarm water. Dry with soft cloth or chamois to prevent spotting.
    DO NOT brush, scrub or scrape these windows.
- After cleaning, rinse thoroughly.

NOTICE Use care when handling decorative windows to avoid scraping or scratching the surface.

#### **GLASS REPLACEMENT**

▲ WARNING DO NOT try to replace the glass yourself.

If glass should need replacement, contact an authorized professional dealer.

#### **AUTOMATIC GARAGE DOOR OPENERS**

If you are installing an automatic garage door opener, installation of a reinforced mounting point is required. To avoid damage to your door, you must reinforce the top section of the door in order to provide a mounting point for the garage door opener to be attached.

**NOTICE DO NOT** use the bracket that came with your opener or attach it directly to the door. Failure to reinforce the door as required may result in damage to the door and result in loss of warranty coverage.

open camera and point



For more information on how to attach an automatic opener, visit: http://clopaypdfs.com/pdf\_files/INST-4150080\_EN.pdf

#### LIMITED WARRANTY

#### ALUMINUM GARAGE DOORS

Subject to the terms of this Limited Warranty ("Warranty") and any warranty policies and procedures in effect at the time a notice of a claim is received, Clopay Corporation ("Clopay", "we", or "our") will repair or replace (at our sole discretion) any garage door sections/section components, hardware, or springs/spring components (collectively, "Replacement Parts") that we determine to be defective in material or workmanship so long as timely written notice is provided within the applicable limited warranty periods provided below. This Warranty shall apply and benefit only the original purchase of a Clopay garage door product and is non-transferable.

The Warranty period begins from the date of delivery. Proof of purchase is required. Once we have verified any defect(s) with your Product through persons authorized by Clopay, we will provide – at no cost to you – Replacement Parts to the extent necessary to repair or replace any such defective sections, hardware, or springs/spring components. We reserve the right to inspect and/or verify any claimed defect, as well as the right to replace Product(s) or its components with a similar or like product or component, all within the sole discretion of Clopay. All labor costs associated with any warranty claim (including removal, reinstallation, installation, and/or finishing) will be your responsibility.

The applicable Warranty periods are as follows:

MODEL NUMBER	PAINT FINISH	SECTIONS/ DELAMINATION	WINDOWS	HARDWARE
AV, AVI, AX, AXU, AZ5, AZ6, AZ5U, AZ6U	Single Family* – 5 Years Other** – 1 Year Color Blast® – 5 Years	3 Years	5 Years (insulated glass)	3 Years

Applies to residential single family installations.

#### ADDITIONAL INFORMATION REGARDING YOUR WARRANTY

Clopay warrants the sections of the Models listed above against the paint finish cracking, checking or peeling (i.e. losing adhesion). Failure to properly clean and maintain your door (particularly in, but not limited to, high-salt or acidic environments) or damage to the door (such as scratching), may result in surface rust, a coating that forms on the surface when exposed to moisture, which – if left untreated — may result in loss of Warranty coverage. Surface rust is not covered under this Warranty. For more information about our rust prevention system and how to care for your door visit: info.garagedoors.com/maintenance

Insulated windows are warranted for five (5) years for material obstruction of vision resulting from film formation or dust or moisture collection between the interior surface of the insulating glass. No warranty is available for single pane glass. No warranty is available for decorative hardware.

#### **EXCLUSIONS TO COVERAGE**

This Warranty shall not extend to damages or defects caused by any of the following:

Paint or Stain Not Applied per Manufacturer Specifications after Delivery of Door	Failure to Follow All Installation Instructions	Failure to Follow Maintenance Instructions	Faulty or Defective Installation(s)
Fire	Radiation (UV or Other)	Foreign Substances	Accident or Casualty
Harmful Fumes	Vandalism	Act(s) of God	Physical Damage
Salt Spray or Exposure	Normal Wear and Tear	Chemical Action	Abrasive Materials
Operation Beyond Rated Capacity	Improper Use or Abuse	Improper Installation or Handling	Exposure to Coastal Weather Conditions
Alteration, Modification or Use of	Other Painted Parts Not Part of a	Normal Fading or Discoloration	Thermal bow as described in DASMA
Non-OEM/Clopay-Approved Parts or Products	Door Section (such as stop mold)	from Usage, Age or UV Exposure	Technical Data Sheet 185 www.dasma.com

If you make any repair or alteration without first providing notice to and receiving authorization from us, or use any parts, accessories, or attachments other than authorized by Clopay for use in its products, you will be solely responsible for any such repairs or parts and you may void this Warranty. Routine maintenance and related items, as well as minor adjustments or damage caused by your installer either during delivery or installation, are excluded from this Warranty. For purposes of this Warranty, minor scratches will not be considered a defect.

If you would like to submit a Warranty claim, notify Clopay Customer Service promptly after discovery of the defect by sending an email to warranty@ clopay.com or calling 800-225-6729. Please be prepared to send us a proof of purchase and complete description with photographs of any issues. YOU MUST REPORT ANY MANUFACTURING DEFECTS THAT ARE IMMEDIATELY OBNIOUS OR VISIBLE AT THE TIME OF INSTALLATION (SUCH AS INCORRECT OR INCONSISTENT PAINT COLOR, MANUFACTURING DEFECTS (E.G. SURFACE CONTAMINANT(S) OR SMUDGES), VISIBLE PHYSICAL DAMAGE, OR MAJOR SCRATCHES) WITHIN FORTY FIVE (45) DAYS FROM DELIVERY OR YOUR CLAIM MAY BE BARRED. Additional copies of our installation and maintenance instructions may be obtained by calling 800-225-6729.

UNDER NO CIRCUMSTANCES SHALL WE BE LIABLE FOR ANY CONSEQUENTIAL OR SPECIAL DAMAGES WHICH ANY PERSON OR ENTITY MAY INCUR OR CLAIM TO INCUR AS A RESULT OF ANY DEFECT IN THE PRODUCT OR IN ANY CORRECTION OR ALTERATION THEREOF MADE OR FURNISHED BY US OR OTHERS. OUR MAXIMUM LIABILITY UNDER THIS WARRANTY SHALL BE THE PURCHASE PRICE PAID TO US WITH RESPECT TO THE GARAGE DOOR TO WHICH SUCH WARRANTY IS CLAIMED. THE LIMITATION OF LIABILITY PROVISIONS HEREIN SHALL APPLY TO ANY AND ALL CLAIMS OR SUITS BROUGHT AGAINST US, INCLUDING ANY CLAIM BASED UPON NEGLIGENCE, BREACH OF CONTRACT, BREACH OF WARRANTY, STRICT LIABILITY OR ANY OTHER THEORIES UPON WHICH LIABILITY MAY BE ASSERTED AGAINST US.

This Warranty constitutes our entire and exclusive warranty as to the Product and is the sole and exclusive remedy for product defects in material and workmanship. We do not assume (and have not authorized any other person to assume on its behalf) any other warranty or liability in connection with any product overed by this warranty. We MAKE NO OTHER WARRANTIES, REPRESENTATIONS OR COVENANTS, EXPRESS OR IMPUED, WITH RESPECT TO THIS PRODUCT, INCLUDING BUT NOT LIMITED TO WARRANTIES, REPRESENTATIONS OR COVENANTS AS TO WORKMANSHIP, DESIGN, CAPACITY, QUALITY, CONDITION, MERCHANTABILITY OR FITNESS FOR ANY PURPOSE OF THE PRODUCT, EXCEPT FOR ANY "IMPLIED WARRANTY" AS THAT TERM IS DEFINED IN THE MAGNUSON-MOSS WARRANTY-FEDERAL TRADE COMMISSION IMPROVEMENT ACT, SUCH IMPLIED WARRANTIES TO BE LIMITED IN DURATION TO A PERIOD OF ONE YEAR FROM THE DATE OF PURCHASE.

This Warranty gives you specific legal rights, and you may also have other rights that vary from state to state.

To the extent of any conflict between this Warranty and any other document, this Warranty shall control. If Warranty is provided in multiple languages, the English language version shall govern.



CORPORATION © 2021 Clopay Corporation. All rights reserved.

<sup>\*\* &</sup>quot;Other" refers to all other residential installations (including installations on facilities owned in common by condominium associations or similar organizations).

INOTALLED DIT									
IID									
UN									
Years									
1	2	3	4	5	6	7	8	9	10
	OUR				Ye	Years	Years	Years	Years

INCTALLED BY:

DOOR INSTALLED ON DATE:

www.clopaydoor.com = 1-800-2CLOPAY (225-6729)

Patents can be viewed at https://www.clopaydoor.com/patents-trademarks

